

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding 755, edding 780

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Acute 1; H400

Aquatic Chronic 2; H411

Asp. Tox. 1; H304

Flam. Liq. 2; H225

Skin Irrit. 2; H315

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS08



GHS09

Signal word

Danger

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

Hazardous component(s) to be indicated on label:

 Naphtha (petroleum), light alkylate
 ETHYLCYCLOHEXANE

Hazard statement(s)

 H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
 P391 Collect spillage.
 P405 Store locked up.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients
3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures
Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Naphtha (petroleum), light alkylate	pls. refer to footnote (1)	
	64741-66-8 265-068-8 649-276-00-X -	Asp. Tox. 1; H304 Flam. Liq. 2; H225 Skin Irrit. 2; H315 Aquatic Chronic 2; H411 STOT SE 3; H336	>= 10.00 - < 25.00 wt%
2	ETHYLCYCLOHEXANE		
	1678-91-7 216-835-0 - 01-2120769125-52-0000	Flam. Liq. 2; H225 Aquatic Chronic 2; H411 STOT SE 3; H336 Aquatic Acute 1; H400 Asp. Tox. 1; H304	>= 10.00 - < 25.00 wt%
3	copper		
	7440-50-8 231-159-6 - 01-2119480154-42	Aquatic Acute 1; H400 Aquatic Chronic 2; H411 Acute Tox. 4; H302	>= 5.00 - < 10.00 wt%
4	zinc powder - zinc dust (stabilized)		

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

	7440-66-6 231-175-3 030-001-01-9 01-2119467174-37	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 2.50 - < 25.00	wt%
5	aluminium powder (stabilised)			
	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45	Flam. Sol. 1; H228	>= 5.00 - < 10.00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	P	-	-	-
5	T	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
3	482 mg/kg bodyweight		

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding**Current version :** 6.0.1, issued: 27.10.2022**Replaced version:** 6.0.0, issued: 10.06.2020**Region:** GB

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); Nitrogen oxides (NO_x); Toxic gases/vapours

5.3 Advice for firefighters

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities**Technical measures and storage conditions**

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: Bases; Acids; oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
----	----------------	---------	--------

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

1	copper	7440-50-8	231-159-6
List of approved workplace exposure limits (WELs) / EH40			
	Copper		
	fume		
	WEL long-term (8-hr TWA reference period)	0.2	mg/m ³
List of approved workplace exposure limits (WELs) / EH40			
	Copper		
	dusts and mists		
	Cu		
	WEL short-term (15 min reference period)	2	mg/m ³
	WEL long-term (8-hr TWA reference period)	1	mg/m ³
2	aluminium powder (stabilised)	7429-90-5	231-072-3
List of approved workplace exposure limits (WELs) / EH40			
	Aluminium metal		
	total inhalable dust		
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
List of approved workplace exposure limits (WELs) / EH40			
	Aluminium metal		
	respirable dust		
	WEL long-term (8-hr TWA reference period)	4	mg/m ³

DNEL, DMEL and PNEC values

DNEL values (worker)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	copper			7440-50-8 231-159-6
	dermal	Short term (acute)	systemic	273 mg/kg/day
	dermal	Long term (chronic)	systemic	137 mg/kg/day
	inhalative	Short term (acute)	systemic	18.2 mg/m ³
2	aluminium powder (stabilised)			7429-90-5 231-072-3
	inhalative	Long term (chronic)	local	3.72 mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	copper			7440-50-8 231-159-6
	oral	Long term (chronic)	systemic	0.16 mg/kg/day
	dermal	Short term (acute)	systemic	273 mg/kg/day
	dermal	Long term (chronic)	systemic	137 mg/kg/day
	inhalative	Short term (acute)	systemic	18.2 mg/m ³
2	aluminium powder (stabilised)			7429-90-5 231-072-3
	oral	Long term (chronic)	systemic	3.95 mg/kg/day

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	ETHYLCYCLOHEXANE		1678-91-7 216-835-0
	water	fresh water	0.63 µg/L
	water	marine water	63 ng/L
	water	Aqua intermittent	6.3 µg/L
	water	fresh water sediment	0.573 mg/kg dry weight
	water	marine water sediment	57.3 µg/kg dry weight

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

	soil	-	0.114	mg/kg dry weight
	sewage treatment plant	-	32	mg/L
2	copper		7440-50-8 231-159-6	
	water	fresh water	7.8	µg/L
	water	marine water	5.2	µg/L
	water	fresh water sediment	87	mg/kg
	water	marine water sediment	676	mg/kg
	soil	-	65	mg/kg
	sewage treatment plant	-	230	µg/L
3	zinc powder - zinc dust (stabilized)		7440-66-6 231-175-3	
	water	fresh water	14.4	µg/L
	water	marine water	7.2	µg/L
	water	fresh water sediment	146.9	mg/kg dry weight
	water	marine water sediment	162.2	mg/kg dry weight
	soil	-	83.1	mg/kg dry weight
	sewage treatment plant	-	100	µg/L
4	aluminium powder (stabilised)		7429-90-5 231-072-3	
	water	fresh water	74.9	µg/L
	sewage treatment plant	-	20	mg/L

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation

liquid

Form

liquid

Colour

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

gold coloured		
Odour		
characteristic		
pH value		
No data available		
Boiling point / boiling range		
No data available		
Melting point/freezing point		
No data available		
Decomposition temperature		
No data available		
Flash point		
Value	7	°C
Ignition temperature		
No data available		
Flammability		
No data available		
Lower explosion limit		
No data available		
Upper explosion limit		
No data available		
Vapour pressure		
No data available		
Relative vapour density		
No data available		
Relative density		
No data available		
Density		
Value	1.03	g/cm³
Reference temperature	20	°C
Solubility in water		
Comments	insoluble	
Solubility		
No data available		
Partition coefficient n-octanol/water (log value)		
No data available		
Kinematic viscosity		
Value	19.0	mm²/s
Reference temperature	40	°C
Type	kinematic	
Particle characteristics		
No data available		

9.2 Other information

Other information		
No data available.		

SECTION 10: Stability and reactivity

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Bases; Acids; Oxidizing agents

10.6 Hazardous decomposition products

Nitrous oxides (NOx)

SECTION 11: Toxicological information
11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity (result of the ATE calculation for the mixture)	
No	Product Name
1	edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding 755, edding 780
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	copper	7440-50-8	231-159-6
LD50	403	- 575	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
2	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	CSR		

Acute dermal toxicity	
No data available	

Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
LC50		5.41	mg/l
Duration of exposure		4	h
State of aggregation	Dust		
Species	rat		
Method	OECD 403		
Source	CSR		
2	aluminium powder (stabilised)	7429-90-5	231-072-3
LC50		0.888	mg/l
Duration of exposure		4	h
State of aggregation	Dust		
Species	rat		
Source	ECHA		

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
Source		CSR	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
Source		CSR	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
Route of exposure		respiratory tract	
Source		CSR	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Route of exposure		Skin	
Source		CSR	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Germ cell mutagenicity	
No data available	

Reproduction toxicity	
No data available	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure	
No data available	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.	

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
LC50		0.75	mg/l
Duration of exposure		96	h
Species		Oryzias latipes	
Method		OECD 203	
Source		CSR	
2	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
LC50		0.169	mg/l

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

Duration of exposure	96	h
Species	Oncorhynchus mykiss	
Method	OECD 202	
Source	ECHA	

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
NOEC		0.056	mg/l
Duration of exposure		116	day(s)
Species	Salmo trutta		
Method	OECD 210		
Source	ECHA		

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
EC50		0.667	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	CSR		
2	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
EC50		0.9	mg/l
Duration of exposure		48	h
Species	Ceriodaphnia dubia		
with reference to	pH < 7		
Method	US EPA 821-R-02-012		
Source	CSR		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
NOEC		82	µg/l
Duration of exposure		7	day(s)
Species	Daphnia magna		
with reference to	pH 6.0		
Source	CSR		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
EC50		0.633	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	CSR		
2	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
EC50		0.3	mg/l
Duration of exposure		72	h
Species	Selenastrum capricornutum		
with reference to	pH > 7 - 8,5		
Method	OECD 201		
Source	CSR		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
NOEC		0.22	mg/l
Duration of exposure		72	h
Species	Algae		
2	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
NOEC		19	µg/l

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

Duration of exposure	7 day(s)
Species with reference to Source	Pseudokirchneriella subcapitata pH 8.0 CSR

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3
EC50		5.2 mg/l	
Duration of exposure		3 h	
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
Value		0 %	
Duration		28 day(s)	
Method	OECD 301 C		
Source	CSR		
Evaluation	not readily biodegradable		

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
BCF		474 - 839	
Method	QSAR		
Source	CSR		

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3
Environmentally hazardous substance mark	Symbol "fish and tree"

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
Technical name	ETHYLCYCLOHEXANE
EmS	F-E, S-E
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	aluminium powder (stabilised)	7429-90-5	231-072-3	75

Trade name: edding Paint Marker-Ink (gold), contained in: edding 750, edding 751, edding 753, edding

Current version : 6.0.1, issued: 27.10.2022

Replaced version: 6.0.0, issued: 10.06.2020

Region: GB

2	copper	7440-50-8	231-159-6	75
3	Naphtha (petroleum), light alkylate	64741-66-8	265-068-8	75
4	zinc powder - zinc dust (stabilized)	7440-66-6	231-175-3	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:

E1, P5b

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information
Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H228	Flammable solid.
H302	Harmful if swallowed.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

P	The harmonised classification as a carcinogen applies unless the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen, in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.
T	This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 25598